



TimeTablet installation

Last updated - Jun 02, 2020 at 2:55PM

Web:	https://timedock.com
Email:	info@timedock.com
International:	(+64) 9 444 1384
Local phone:	(09) 444 1384

Installing the TimeTablet requires only a few minutes, a philips-head screw driver and the contents of the product.

Step 1: Remove mounting bracket from the device

Use the special security allen-key provided to remove the two pivot-adjustment bolts from the mounting bracket. This will disassemble it into two parts allowing you to attach the base to the wall.

Step 2: Attach mounting bracket to the wall

Screw the base-section of the mounting bracket to the wall using the fasteners provided. Take care to ensure that the bracket is level.

Step 3: Attach electrical conduit (optional)

For a nice and tidy finish we recommend concealing the power cable with electrical conduit or similar.

Step 4: Attach TimeTablet to the wall

Re-attach the TimeTablet to the base-section of the mounting bracket from Step 2.

Step 5: Setup device

Turn the device on by holding down the power button on the top-right of the TimeTablet for a few seconds. Upon booting, the TimeTablet screen will display. To ensure the device can upload data to TIMEDOCK.com you will need to connect it to a WIFI or 3G data connection. To initiate this process, tap the 'Master Key' card (provided with the device) to the card reader symbol on the left-hand side. A screen with admin options will appear including a 'Connect WiFi' option.